

PLANZICHT

The plan view shows a rectangular drainage structure divided into three sections: **UITRIT** (Exit), a central grate area, and **INRIT** (Entrance). The overall width is 2835 mm.

Dimensions:

- Total width: 2835 mm
- Grate width: 1220 mm
- Distance from left wall to grate start: 370 mm
- Distance between grates: 600 mm
- Distance from grate end to right wall: 250 mm
- Left side depth segments: 20, 25, 135, 40, 135, 25, 20 mm (Total 400 mm)
- Right side depth segments: 20, 25, 135, 40, 135, 25, 20 mm (Total 400 mm)

Slopes:

- Left side slope: 4.5% (downwards)
- Right side slope: 6.0% (downwards)

Structural Details:

- Reinforcement bars are shown as vertical lines across the grate area.
- Two arrows point to the bottom of the grate area with the note: "doorvoeren Ø110mm en Ø90mm t.b.v. verversen van reinigingswater"

Section Lines:

- Horizontal section line A-A (dashed blue line) passes through the center.
- Vertical section line B-B (dashed blue line) passes through the center.

doorvoeren Ø90mm en Ø110mm
t.b.v. verversen van reinigingswater

400
20 360 20

15
+11.22mTAW
+11.02mTAW
+11.63mTAW
+10.31mTAW

20 15 11 16 55 82 20

principe detail folie
±70cm onder afgewerkt peil

25 135 40 135 25

betonnen kuip
verdichte ondergrond

Beton

Verdichte ondergrond
in gestabiliseerd zand

Water

HET ONTWIKKELEN VAN EEN SITE EN DE NIEUWBOUW VAN 2 HALLEN VOOR SLIBOPSLAG EN EEN WERKPLAATS

datum:	03/07/2025	plannr:	A22
schaal:	1 : 100	index:	PIV1
projectcode:	JDBK-220025	tekenaar:	dvm